



CAVIBLASTER™

Model - 1620

Specifications and Options

SKID	
Dimensions:	
Height	30" / 76 cm
Width	32" / 81 cm
Length	47" / 119 cm
Weight	600 LBS / 272 kg
Fuel - Oil Containment Pan	Yes
Lifting Eyes / Fork Slots	Yes / Yes

PUMP SYSTEM	
Pressure Pump*	Udor NX 75/150
Pump Material / Type	N.A.B. / Positive Displacement
Flow Rate	16 GPM / 61 lpm
Nozzle Pressure	2,000 PSI / 138 Bar
Hose Diameter / Max. Length	3/4" / 600 LF – 19 mm / 200m

FEED SYSTEM	
Feed Pump	12V Submersible
Pump Body / Shaft	Thermoplastic / SS
Flow Rate	37 GPM / 140 lpm

DRIVE SYSTEM	
Engine	Kohler KD625-2
Engine Type	2-Cylinder - 4-Cycle
Cooling System	Air
Combustion System	Direct Injection
Output Maximum HP/kW	25 / 19
Output Continuous HP/kW	23 / 17
Clutch	Centrifugal
Starting System	Electric
Emergency Shut-off	Yes

*Options include CAT Pump 1531AAF or General Pump KE28A

